EUROTECHNIQUE

SPIDERCUT 5

Ref. 1MEAYsizes 8>>11

13 Gauge



DESCRIPTION

Seamless glove with HPPE yellow fluo support 13G cut 5.

Coated black nitrile foam with seeded effect on the palm which guarantee an excellent grip.

Reinforcements in TPR, sewn Kevlar, on the back of the hand and on the phalanges offering optimal protection against impacts

Ergonomic padding on the palm.

Reinforcements between the thumb and the index to icrease the shelf life of the glove.

Wrist tightening by Velcro.

CUT RESISTANCE GLOVES




- Maximal protection against the cuts
- Phalange and back protection of the hand against impacts
- Reinforcements on the palm and the thumb for more confort and a longer shelf life
- High-visibility



SIZES	REFERENCE
8	1MEAY08
9	1MEAY09
10	1MEAY10
11	1MEAY11

PACKAGING



APPLICATION DOMAIN



Building

Oil industry

Community





STANDARD



This glove is in conformity with the model of the individual safety equipment which corresponds to **8480 Issue 2**.

Delivered by **SATRA (0321)**

EN 420:2003 + A1:2009



EN 388:2003

A B C D 4 5 4 3



- Resistance to abrasion (4/4)
- Resistance to blade cut (5/5)
- Resistance to tear (4/4)
- Resistance to puncture (3/4)